

KS-C48G-TU-6YQ





● سه سال گارانتی پلاتینیوم بدون قید و شرط کی دی تی شامل:

● آپزوردگی، شکستگی، ضربه دیدگی، خسارت ناشی از صاعقه، زنگ زدگی، نویسانات برق و سایر اتفاقات و صدمات

عملکردهای اصلی

- دارای ۴۸ پورت PoE با سرعت ۱ گیگابیت
- دارای ۴ پورت UP-Link با سرعت ۲۵ گیگابیت
- دارای ۲ پورت UP-Link با سرعت ۴۰ گیگابیت
- نمایش وضعیت پورت ها از طریق LED
- دارای منبع تغذیه دوگانه
- دارای سیستم تهویه سرویس پذیر
- قابلیت برنامه ریزی دستگاه از طریق وب
- قابلیت برنامه ریزی از طریق پورت Console و Telnet
- دارای توان ۲۲۰۰ وات



Interface	
Total Port	56 Ports
POE Output (Max)	2200W
PoE Standard	IEEE802.3bt (PoE++)
Gigabit RJ45 POE Port	48 * 10/100/1G BASE-T
SFP28 Uplink Port	4
QSFP Uplink Port	2
QSFP28 Uplink Port	N/A
Management Ports	1*Console Port (RJ45) 1* Ethernet Management Port (RJ45)
Hardware	
CPU	Dual-core processor
Flash Memory	8GB EMMC (OS) 4MB SPI Flash (Boot)
DRAM	4GB
Fans	2*Hot-swappable Fan
Airflow	Front-to-Rear
Switching Capacity	456Gbps (bidirectional)
Forwarding Rate	678.53Mpps (bidirectional)
MAC address	98304
Switching Hardware Platform	
Jumbo Frame	9600
MAC scale	98,304 unicast, 2,048 multicast
VLANs	4,094 IDs, 4,094 instances
Link aggregation	64 groups, convergence <50 ms
Protection	STP (<30s), RSTP/MSTP (<1s), ERPS (<50 ms)
OAM	IEEE 802.1ag CFM, 1,024 sessions, CCM intervals down to 3-3 ms
Routing scale	IPv4 FIB up to 57,344; IPv6 FIB up to 6,144
QoS	Per-port queues, granular policing/shaping, IPFIX visibility
Security	MACsec, ACLs, DHCP Snooping, IP Source Guard

Software Highlights	
Software License	EB, Basic L3 software features, Preinstalled MS, L3 enhance features software license key
Basic License (Pre-installed)	VLANs, QinQ, STP/RSTP/MSTP, IGMP Snooping, static IPv4 routes, VRRP, ACLs, DHCP Snooping, QoS policing/shaping, SNMP/Web/CLI
Advanced License (Optional)	OSPFv2/v3, BGP, IS-IS, PIM-SM/DM, IPv6 routing, MPLS/VPLS, VXLAN with BGP EVPN, ERPS multi-ring, advanced OAM (8 02.1ag, Y.1731), MACsec, sFlow/IPFIX, RPC-API, Smart Config
General	
Protection Rating	IP51
Web Language	English
Dimension (W*H*D)	442*44*410mm
Weight	8.36kg
Storage Temperature	-40°C to 70°C
Operating Temperature	0°C to 45°C
Storage Humidity	0 to 95% (Non-condensing)
Operating Humidity	10% to 90% (Non-condensing)
Temperature Alarm	50°C
Altitude	5000m
Power Supply	
Power Supply	2*1200 W hot-swappable PSU
Redundant	Yes
LED Power	Yes
Power consumption	72W
Guarantee	
Product Guarantee	3 Years Platinum Guarantee
MTBF	≥90000h (~10.3 Years)