KV-N2S4-PF/V2

2.4" | SIP | HAC | Conference | HD | PoE | 100M

3 YEARS PLATINUM GUARANTEE

- سه سال گارانتی پلاتینیوم بدون قید و شرط کی دی تی شامل:
- آبخوردگی، شکستگی، ضربه دیدگی، خسارت ناشی از صاعقه، زنگ زدگی، نوسانات برق و سایر اتفاقات و صدمات

عملکردهای اصلی

- قابلیت پشتیبانی از 4 حساب SIP برای تماس ها
- امکان برقراری کنفرانس تلفنی با 6 شرکت کننده
- قابلیت اشتراک گذاری یک خط SIP با دستگاه های دیگر
- 3 کلید قابل برنامه ریزی برای خطوط تلفن در صفحه نمایش اصلی
- صفحه نمایش رنگی 2.4 اینچی به عنوان نمایشگر اصلی
- کیفیت صدای بالا (HD) هنگام استفاده از اسپیکرفون و گوشی تلفن
- سازگاری با هدست‌های بی‌سیم EHS (Electronic Hook Switch)
- دارای دو پورت شبکه با سرعت مگابیت و پشتیبانی از PoE برای تامین برق از طریق کابل شبکه
- دارای پایه های با قابلیت تنظیم در دو زاویه 45 و 50 درجه
- سازگار با پلتفرم های مطرح مانند Asterisk، Elastix، Metaswitch، 3CX، Broadsoft، Avaya و غیره



Generic	
Specification	4 SIP Lines HD Voice PoE Enabled 2.4-inch color screen
Phone Functions	Local Phonebook (1000 entries) Remote Phonebook (XML/LDAP, 1000 entries) Call logs (In/Out/Missed, 1000 entries) Programmable DSS/Soft keys VMWI
Call Functions	Call out/Answer/Reject Mute/Unmute (Microphone) Call Hold/Resume Call Waiting Intercom Caller ID Display Call Forward (Always/Busy/No Answer) Call Transfer (Attended/Unattended) 6-way Audio Conference
Video	N/A
Audio	
Audio	HD Voice: HD handset, HD speaker Wideband ADC/DAC 16KHz Sampling
Narrowband Codec	G.711a/u, G.723.1, G.726, G.729, G.729A, G.729B, G.729AB, ILBC
Wideband Codec	G.722, Opus
Network	
Physical	10/100 Mbps Ethernet, dual bridged port for PC bypass
IP Mode	IPv4/IPv6/IPv4&IPv6
IP Configuration	Static IP,DHCP,PPPoE, 802.1x, Network Access Control
VPN	L2TP,OpenVPN
VLAN	VLAN / LLDP / Qo5/ RTCP-XR (RFC3611), VQ-RTCPXR, (RFC6035)
Protocols	
SIP v1 (RFC2543) v2(RFC3261); Support SIP v2 protocol with RFCs 2474, 3261, 3263, 3264, 3265, 3550, 4566, 5359, 6086; UDP/TCP/TLS; RTP/RTCP/SRTP(Optional/Compulsory); STUN; DHCP; IPv6; LLDP; PPPoE; 802.1x; QoS: 802.1p/Q (VLAN) ,Layer 3 ToS; MPLS; L2TP; OpenVPN; SNTP; FTP/TFTP; HTTP/HTTPS; TR-069; AES128 & AES256; SHA-256 & SHA-256-sess; SHA-512/256 & SHA-512/256-sess; MD5-sess	

Deployment & Management	
Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069, Screenshot, Web Management Portal, Web-based Packet Dump, Configuration Export / Import, Phonebook Import/Export, Firmware Upgrade, Syslog, Network Firewall, Online Upgrade	
Physical Specifications	
Main LCD x1	2.4-inch (320x240) Color Screen
DSS Key-mapping LCD x2	N/A
Keypad	35 keys including 4 Soft-keys 8 Function keys (Hold/Transfer/Voice message/Conference/Phonebook/MWI/Headset/Redial/Hands-free), 3 Line keys (With LED Indicator Light), 4 Navigation keys, 1 x OK key, 12 Standard Phone Digits keys, 3 Volume Control keys (Up/Down/Mute (Microphone))
HD Handset	1 x (RJ9)
Standard RJ9 Handset	1 x Wire
Status Indicator Light	x1 (Red)
RJ9 Port x 2	Handset x1, Headset x1
RJ45 Port x2	Network x1, PC x1 (Bridged to Network)
Safety Keyhole	x1
Power Input	DC 5V/1A or PoE
Power Consumption (PoE)	1.32~2.09W
Working Humidity	10~95%
Working Temperature	0~45°C
Installation	Desktop Stand; Wall mountable (optional)
Color	Black
Dimensions	178x191x171 mm (Desktop Stand)

بدون اطلاع قبلی حق تغییر در شکل ظاهری و ارتقا مشخصات فنی محفوظ می باشد .