Cat6 Cable UTP-SFTP

NC-Cuprum 6UTP

Conductor	
Size	23 AWG
Design Type	Spacer / Copper Wires / 1 Jacket
Diameter (mm)	0.55 ± 0.5
Insulation	
Type	UTP
Cable Diameter	Nom. 5.5±0.5 mm
Jacket Thickness	Nominal Thickness = 0.56 mm
Shielding	N/A
Physical	
1. Cold Bend Test	-30 ± 2°C X 4hrs no crack
2. Dielectric strength	AC 1.7KV for 2s
Jacket	
Min Bending Radius	50 mm
Installation Temperature	-10°C to +60°C
Type	PVC
Overall Diameter	6.1 ± 0.3 mm





NC-Cuprum 6SFTPI

Conductor	
Size	23 AWG
Design Type	Spacer / Copper Wires / 1 Jacket/Shield/Foil
Diameter (mm)	0.5 ± 0.55
Insulation	
Type	SFTP-Indoor
Cable Diameter	Nom. 5.5±0.5 mm
Jacket Thickness	Nominal Thickness = 0.56 mm
Shielding	Aluminium / Polyester Foil
Physical	
1. Cold Bend Test	-30 ± 2°C X 4hrs no crack
2. Dielectric strength	AC 1.7KV for 2s
Jacket	
Min Bending Radius	50 mm
Installation Temperature	-10°C to +60°C
Type	PVC
Overall Diameter	8.1 ± 0.3 mm

NC-Cuprum 6SFTPO

Conductor	
Size	23 AWG
Design Type	Spacer / Copper Wires / 1 Jacket/ Shield/Foil
Diameter (mm)	0.5 ± 0.55
Insulation	
Type	SFTP Outdoor
Cable Diameter	Nom. 5.5±0.5 mm
Jacket Thickness	Nominal Thickness = 0.59 mm
Shielding	Aluminium / Polyester Foil
Physical	
1. Cold Bend Test	-30 ± 2°C X 4hrs no crack
2. Dielectric strength	AC 1.7KV for 2s
Jacket	
Min Bending Radius	50 mm
Installation Temperature	-10°C to +65°C
Type	Polyethylene
Overall Diameter	8.3 ± 0.3 mm



بدون اطلاع قبلی حق تغییر در شکل ظاهری و ارتقا مشخصات فنی محفوظ می باشد.